


HDM-320-4K

32" 4K/HD/SD-SDI Video Monitor



12-bit Ultra HD LCD screen supports up to 4 channels of 3G/HD/SD-SDI. 3840 x 2160 resolution. In-screen audio level meters, vectorscope and waveform.

The HDM-320-4K-TT monitor sets a new standard in UltraHD LCD monitors for broadcast and professional video applications. It provides a 32", 3840 x 2160 resolution, 16:9 format, 60Hz refresh, anti-glare IPS LCD screen. All video formats are scaled to fit on the screen in the highest quality using 12-bit digital processing, precision scaling and gamma correction to produce the best images possible.



Features/Benefits

- Monitor 2SI Interleave or Quad-Link 4K video using the four HD-SDI inputs together
- Two display modes: single display and quad link display.
- Each of 4 SDI inputs can be displayed by full screen in single mode. Quad link mode supports 2-SI and square division display
- User-defined hot key functionality for either H/V delay, underscan, on-screen display
- On-screen, 16-channel level metering provides audio confidence monitoring
- Tally and on-screen labeling provide quick and easy signal identification
- CRT-style image controls allow video image enhancement for each screen individually
- Supports multi-format analog and digital audio signals
- Allows adjustment of the parameters for each screen
- Provides high-quality waveform or vector monitoring (for SDI)
- User-adjustable color temperatures with presets
- Ethernet, RS-485 and GPI control interfaces

Part Numbers:
HDM-320-4K-TT 8001-0630

32" UltraHD IPS LCD Video Monitor, 4 x 3G/HD/SD-SDI BNC Inputs
Audio/Video Metering. Tabletop Stand.

HDM-320-4K


32" 4K/HD/SD-SDI Video Monitor

Block Diagram



Rear View

HDM-320-4K Series Block Diagram



Specifications

Display Type	Active color matrix amorphous LCD IPS with LED Backlight
Display Size	32" Diagonal.
Resolution	1920 H x 1080 V
Aspect Ratio	16:9,4:3
Viewing Angle	178° x 178°
Luminance	300 cd/m2
Colors	1.073G colors
Contrast	3000:1
Screen Resolution	3840(H) x 2160(V)
Input Signal Format	HD/3G - 720p24/23.97 720p25 720p30/29.97 720p50, 720p60/59.94 1080sf24/23.97 1080sf25 1080sf29.97 1080sf30 1080i50 1080i60/59.94 1080p24/23.97 1080p25 1080p30/29.97 1080p50 1080p60/59.94 2K 1080p50 1080p60/59.54 4K 4096x2160p60/59.94 4096x2160p50 3840x2160p60/59.94 3840x2160p50
Speakers	2 x 5W speakers, headphones
Audio Outputs	1 Selected Pair: 1/8" Headphone jack
Supplied Accessories	Power adapter, AC Power cord
Dimensions inc. Stand (H x W x D)	28.3" H x 17.4" W x 2.8" D 720 mm H x 442 mm W x 78 mm D
Weight with Stand	13 lbs. (5.9 kg)
Power Connector	AC power adapter (100-240VAC to 12 VDC)
Power Requirements	AC power adapter connects to mains power (100 to 240 VAC ± 10%, 50/60Hz)
Power Consumption	44W

Specifications subject to change, errors and omissions excepted.
All trademarks, product names and logos are the property of their respective owners.
Any rights not expressly granted herein are reserved. ©2016, Wohler Technologies Inc.
version:APR16